

STERLING SRA320 AUTO DOWNFEED BAND SAW



The Sterling SRA320 and SRA320 L models with auto downfeed operation are ideal for cutting a wide range of profiles, although being especially suited to cutting tubes and solid bar stock. A blade speed inverter is standard giving these machines the capacity to cut a wide range of material types including more exotic materials.

FEATURES

- Auto downfeed with variable cutting pressure
- Mitre 45° right by turning the vice clamps
- Manual Vice
- Carbide blade guides for high accuracy
- Coolant system
- Safety interlock switches fitted to band cover
- Blade speed inverter
- Hydraulic blade tension indicator.
- Safety control panel situated away from the blade.

OPTIONS

- Spray mist cooling system (requires compressor)
- Roller track and measuring systems

TECHNICAL INFORMATION

MODEL		SRA320
Capacities		
Tube at 90°	mm	320
Square Section at 90°	mm	320
Rectangular Section / Beam at 90°	mm	400 x 220
Tube at 45°	mm	280
Square Section at 45°	mm	260
Rectangular Section / Beam at 45°	mm	280 x 200
Blade Size	mm	3660 x 27 x 0.9
Bed Height	mm	640
Cutting Speed	m/min	20 - 100
Motor	kW	1.5
Length	mm	1900
Width	mm	850
Height	mm	1300
Weight	Kg	570
Operation		Auto down feed
Vice		Manual

OTHER IMAGES

