

STERLING SRC315 X CIRCULAR SAW 415V



The heavy construction and quality finish of the Sterling SRC range of circular sawing machines is outstanding. Models with 275, 315 and 350mm diameter blades are offered as not only the standard pull down version – with or without a pneumatic vice system – but also in a fast cutting semi-automatic design for production cutting. Double clamping and self-centring vices ensure material is always securely clamped in the optimum cutting position.

FEATURES

- Heavy duty construction
- High quality gearbox in oil bath
- Pull down operation
- Double head return springs
- Quick set mitring 45° left and right
- Pneumatic vice operation
- Double clamping anti-burr vice
- Self centring vice to ensure cutting is in optimum position
- 2 speed motor
- Electrical coolant pump
- Coolant resevoir in base with return filter
- Adjustable length stop bar

OPTIONS

- Roller track and measuring systems

TECHNICAL INFORMATION

MODEL		SRC315 X
Capacities		
Tube at 90°	mm	105
Square Section at 90°	mm	85
Rectangular Section / Beam at 90°	mm	120 x 70
Tube at 45° L & R	mm	90
Square Section at 45°	mm	80
Rectangular Section / Beam at 45°	mm	90 x 60
Blade Diameter	mm	315
Blade Bore	mm	32
Blade Speeds	rpm	45 / 90
Motor	kW	1.3 / 1.8
Length	mm	1100
Width	mm	600
Height	mm	1400
Weight	Kg	210
Operation		Pull Down
Vice		Pneumatic

OTHER IMAGES

