

STERLING SRE350 R CIRCULAR SAW 415V



The heavy construction and quality finish of the Sterling range of circular sawing machines is outstanding. The SRE models feature the main vice clamp to the left of the blade with a removable anti-burr clamp to the right of the blade; this brings flexibility to perform operations such as cutting tubes close to a bent elbow. The SRE350 R model is of a pull down design with manual clamping and easy mitring to 45° both left and right. The SRE350 is also available with pneumatic clamping or in a fast cutting semi-automatic design for production cutting.

FEATURES

- Heavy duty construction
- High quality gearbox in oil bath
- Pull down operation
- Double head return springs
- Quick set mitring 45° left and right
- Main clamping vice to left of blade
- Anti-burr offcut clamping device to right of blade
- 2 speed motor
- Electrical coolant pump
- Coolant reservoir in base with return filter
- Adjustable length stop bar

OPTIONS

- Roller track and measuring systems

TECHNICAL INFORMATION

MODEL	SRE350 R	
Capacities		
Tube at 90°	mm	115
Square Section at 90°	mm	100
Rectangular Section / Beam at 90°	mm	120 x 80
Tube at 45° L & R	mm	110
Square Section at 45°	mm	90
Rectangular Section / Beam at 45°	mm	90 x 90
Blade Diameter	mm	350
Blade Bore	mm	32
Blade Speeds	rpm	45 / 80
Motor	kW	1.3 / 1.8
Length	mm	1000
Width	mm	600
Height	mm	1400
Weight	kg	210
Operation	Pull Down	
Vice	Manual	

OTHER IMAGES



SRE X pneumatic vice model pictured