

## BISON ROLLER TRACK SYSTEM

The Bison stand alone gravity roller track systems are adjustable for height and available in 1000mm, 2000mm and 3000mm lengths. The track systems are manufactured to the bed height of the associated machine, which can finally be adjuste +/- 50mm for levelling purposes. A selection of load ratings and roller widths provide a material handling solution for virtually all bandsaws.

The Bison range of rollers are available in varying diameters, lengths and load ratings. Each roller is supplied with heavy duty machined bearings and spring loaded telescopic axial pins and are ideal for companies who desire to manufacture their own roller track.

### FEATURES

- Heavy duty machined bearings
- Fully adjustable modular system
- Large selection of load capacities
- Available in 1000, 2000 & 3000mm lengths
- Available in 6 different widths

### OPTIONS

- Bespoke track sizes
- Vertical rollers
- Motorised systems



### TECHNICAL INFORMATION

STOCK CODE	WIDTH mm	LENGTH mm	ROLLER Ø mm	HEIGHT mm	NO OF ROLLERS	MAX. CAPACITY Kg UDL	FRAME SIZE RSA mm
15600	250	1000	50 x 2	610-960	4	375	50x50x5
15601	250	2000	50 x 2	610-960	6	560	50x50x5
15602	250	3000	50 x 2	610-960	10	935	50x50x5
15603	350	1000	50 x 2	610-960	4	375	50x50x5
15604	350	2000	50 x 2	610-960	6	560	50x50x5
15605	350	3000	50 x 2	610-960	10	935	50x50x5
15609	350	1000	60 x 2	610-960	4	545	75x50x6
15610	350	2000	60 x 2	610-960	6	815	75x50x6
15611	350	3000	60 x 2	610-960	10	1360	75x50x6
15612	450	1000	60 x 2	610-960	4	545	75x50x6
15613	450	2000	60 x 2	610-960	6	815	75x50x6
15614	450	3000	60 x 2	610-960	10	1360	75x50x6
15618	450	1000	63.5 x 3	610-960	4	920	75x50x6
15619	450	2000	63.5 x 3	610-960	6	1380	75x50x6
15620	450	3000	63.5 x 3	610-960	10	2295	75x50x6
15621	550	1000	63.5 x 3	610-960	4	920	75x50x6
15622	550	2000	63.5 x 3	610-960	6	1380	75x50x6
15623	550	3000	63.5 x 3	610-960	10	2295	75x50x6
15627	650	1000	76.4 x 3	610-960	4	1530	100x50x6
15628	650	2000	76.4 x 3	610-960	6	2295	100x50x6
15629	650	3000	76.4 x 3	610-960	10	3825	100x50x6
15630	750	1000	76.4 x 3	610-960	4	2210	100x50x6
15631	750	2000	76.4 x 3	610-960	6	3315	100x50x6
15632	750	3000	76.4 x 3	610-960	10	5525	100x50x6